





Amfold-Q
with Amstack D

(Amscan is optional)

Quality sheet folder, with various crossfolding, various crossfold speeds and all knife crossfolds

Specification

Standard Features: Amfold-Q

- Single lane or multiple lanes
- 2 Primary folds
- Up to 3 cross folds
- Automatic operation
- Program control from Feeder
- Crossfolds speed adjustable for each program
- Several cross fold combinations available
- Oblique sheet detection before cross fold
- Double driven 1st cross fold rollers
- Able to connect with any Ironer
- Photocells face down without mirror
- PLC touch screen
 - Pneumatic folding
 - Standard Ethernet connection
 - Programmable for different types of linen
 - Ocunting linen in each lane, linen folds per day
 - USB stick connection for backing up of settings

Standard Features: Amstack-D

- Voltage 380 v / 50 Hz / 3 Ph
- Programmable pieces stacked from 1-18 pieces
- Microprocessor control to work as a single unit with Folder
- Attach to a Folder at either end and synchronize with a Folder

Technical Information:

Electrical

Voltage : 3x380 V+N+PE / 50 Hz
 Power : 1.25-2 kW, Fuses 10A

Pneumatic

Pressure : 6 -10 Bar

Consumption : 20-30 KNL/1000 sheets

• Connection : 3/8" (1/2" tube)

Miscellaneous

Noise level: 75 dBA

Speed : 8 up to 50 m/min

Production Materials

Sheets (with crossfolds)

• Sheets, table linen, draw sheets, etc.

Max. size 1 lane : 3.0 m x 3.0 mMin. size 1 lane : 0.9 m x 0.9 m

Small pieces

Max. size multilane : 1.3 m x lane width

Min. size multilane : 0.4 m x 0.25 m

Specification of design is subject to change without notice. For additional options please consult factory and distributor.















