



# Washer

Extractor

**HXC Series (Coin Equipment)**

MODEL: HXC-22, HXC-35, HXC-50, HXC-65

# SPECIFICATION

## Standard Features :



- All wetted parts are 304 (18/8) stainless steel
- 3 or 4 compartments supply dispensers
- 30-cycle microprocessor
- 150G extraction force
- 5 degree lean back for strength and easier loading
- Built in vacuum breaker
- Variable speed frequency inverter

## Optional Features :

- Direct Steam Heating
- Electrical Heating
- EMI Filter for CE
- Special Voltage Modifications

Model			HX-22	HX-35	HX-50	HX-65
<b>Units of Measurement</b>	<b>Matric</b>	<b>US</b>				
Maximum Capacity	kg.	lbs.	10 (22)	16 (35)	23 (50)	29 (65)
<b>Overall Dimensions :</b>						
A - Machine Width	mm.	inch	660 (25.98")	769 (30.27")	769 (30.27")	878 (34.56")
B - Machine Depth	mm.	inch	905 (35.62")	1025 (40.35")	1133 (44.60")	1196 (47.20")
C - Machine Height	mm.	inch	1013 (39.88")	1133 (44.72")	1229 (48.38")	1331 (52.40")
<b>Cylinder Information :</b>						
Basket Diameter	mm.	inch	535 (21.06")	610 (24.01")	680 (26.77")	790 (31.10")
Basket Depth	mm.	inch	408 (16.06")	498 (19.60")	580 (22.83")	595 (23.42")
Basket Volume	cu.m	cu.ft	0.09 (3.24")	0.15 (5.14")	0.21 (7.44")	0.29 (10.30")
<b>Door Opening and Height :</b>						
Door opening Diameter	mm.	inch	302 (11.88")	365 (14.37")	365 (14.37")	450 (17.71")
Height of Door Bottom Above Floor	mm.	inch	378 (14.88")	420 (16.35")	486 (19.13")	507 (19.96")
<b>Drive Information :</b>						
Number of Motors	Number		1	1	1	1
Size of Motor	kW	HP	0.75 (1)	1.5 (2)	2.2 (3)	3 (4)
<b>Cylinder Speeds :</b>						
Wash	RPM	G-Force	52 (0.8)	49 (0.8)	46 (0.8)	44 (0.8)
Distribution	RPM	G-Force	82 (2)	77 (2)	74 (2)	68 (2)
Extract	RPM	G-Force	818 (200)	766 (200)	725 (200)	674 (200)
<b>Water Inlets and Consumption :</b>						
Hot Water Size	NPT		3/4"	3/4"	3/4"	3/4"
Cold Water Size	NPT		3/4"	3/4"	3/4"	3/4"
Additional Water Inlet	NPT		3/4"	3/4"	3/4"	3/4"
Average HOT Water Consumption/Cycle	liters	gal	91 (24)	91 (24)	193 (51)	223 (59)
Average COLD Water Consumption/Cycle	liters	gal	174 (46)	174 (46)	102 (27)	106 (28)
<b>Drain Outlets and Capacity :</b>						
Number of Drains	Number		1	1	1	1
Drain Size	mm.	inch	50.8 (2")	50.8 (2")	50.8 (2")	76.2 (3")
Drain Capacity	liters/min	gpm	117 (31)	117 (31)	310 (81.9)	581 (153.5)
<b>Steam Inlet and Consumption :</b>						
Steam Inlet Connection	NPT		1/2"	1/2"	1/2"	1/2"
Steam Pressure	bar	Psi	6 (100)	6 (100)	6 (100)	6 (100)
Steam Consumption	kg/hr	lb/hr	N/A	N/A	N/A	N/A
<b>Weight and Shipping Information :</b>						
Net Weight (approx.)	kg.	lbs.	201.50 (444)	283.80 (625.70)	351.90 (775.80)	431 (950.20)
Domestic Shipping weight (approx.)	kg.	lbs.	216.50 (477.30)	298.80 (658.70)	367.40 (809.90)	540 (1190.50)

Specification of design is subject to change without notice. For additional options please consult factory and distributor.



ISO 9001 : 2015



ISO 14001 : 2015



ISO 13485 : 2016



ISO 45001 : 2018

ACCURATE TECHNOLOGIES CO., LTD.

Bangkok, Thailand Phone : +66(0)2740-5511 (Auto) Fax : +66(0)2752-2773

Website : [www.imagelaundrysystems.com](http://www.imagelaundrysystems.com) Email : [sales@imagelaundrysystems.com](mailto:sales@imagelaundrysystems.com)

Rev. 2026-001